



Box unit on truck	Length (m)	TARE +/- 3% (Kg)		
		2 decks	3 decks	4 decks
	6.8 (6.0-7.5)	3400 (3200-3600)	3900 (3700-4100)	4400 (4200-4600)

TECHNICAL CHARACTERISTICS

- Ø **structure:** self-supporting anti-corrosion Aluminium structure connected to the main chassis by means of galvanized counter-frame
- Ø **box unit:** self-supporting box unit with 2, 3, or 4 hydraulically powered loading decks, hydraulic roof, side and rear doors, oil tank, tool box; internal and external working lights
- Ø **hydraulic:** complete with automatic safety devices in accordance with Machines Directive and Work Safety Institute (TÜV approval n° 24 03 9761 002)
- Ø **loading ramp:** hydraulic, foldable type, automatically balanced, antiskid, side safety barriers
- Ø **partitions gates:** Aluminium or galvanized steel gates with upper extension for bovines
- Ø **roof:** sandwich structure with internal insulation
- Ø **drinking system:** automatic type with nipples for pigs, sheep and bowls for bovines and water tank 250l

OPTIONALS

- Ø vents with Aluminium flaps
- Ø independently powered loading decks
- Ø forced ventilation system (fans)
- Ø GPS positioning system integrated with temperature control system and opening doors recording, data logger and GPRS transmission