



| MODEL | GROSS WEIGHT (Kg) | LENGTH (m) | TARE +/- 3% (Kg) | | |
|--------|-------------------|------------|------------------|---------|---------|
| | | | 2 Decks | 3 Decks | 4 Decks |
| RBA32E | 27000 | 7.10 | 7100 | 7600 | 8000 |
| RBA32F | 27000 | 7.60 | 7250 | 7800 | 8250 |
| RBA32G | 27000 | 8.10 | 7400 | 8000 | 8500 |

TECHNICAL CHARACTERISTICS

- Ø **Chassis:** Self-supporting anti-corrosion Aluminium structure
- Ø **Axles:** twin 10000 Kg capacity.
- Ø **Brakes:** disk Ø 370 mm.
- Ø **Braking system:** pneumatic with 2 lines according to ECE regulations with 4 channel EBS and RSS.
- Ø **Parking Brakes:** spring brakes with pneumatic controls.
- Ø **Suspensions:** pneumatic type with electronic control and integrated with front and rear stabilization bar.
- Ø **Wheels:** disc 19.5 x 7.50 and M spigot.
- Ø **Tyres:** 265/70R19.5 or 255/60R19.5 twin.
- Ø **Draw bar:** extensible tow bar 12x50 mm - table bearing Ø 1200 mm.
- Ø **Body:** box unit for livestock 2, 3, or 4 loading decks with hydraulic controls, raising lowering roof, side doors and back doors, wide tool boxes under the body, internal and external working lights.
- Ø **Electrohydraulic system:** completed with automatic safety device in accordance with Machines Directive and Work Safety Institute. (approval TUV n° 24 03 9761 002)
- Ø **Loading ramp:** with hydraulic movement, anti-slip, with incorporated side guards and to work as barn doors if necessary
- Ø **Partition gates:** in aluminium or zinc coated steel with over-flap for larger animals.
- Ø **Roof:** insulated type

OPTIONALS

- Ø Vents on sided to be closed with aluminium flaps (+300 Kg);
- Ø Automatic drinking system with water tank (+250 Kg);
- Ø Heating system for drinking system
- Ø Positioning GPS system integrated with temperature and opening doors recording.