



GROSS WEIGHT (Kg)	LENGTH (m)	TARE +/- 3% (Kg)				
		2+2 Decks	2+3 Decks	3+3 Decks	3+4 Decks	4+4 Decks
42000	17.30	12300	13100	13500	14300	14700

TECHNICAL CHARACTERISTICS

- Ø **Chassis:** Self-supporting anti-corrosion Aluminium structure
- Ø **Axles:** twin 10000 Kg capacity - 1st liftable, 2nd fixed, 3rd steering.
- Ø **Brakes:** disk Ø 370 mm.
- Ø **Braking system:** pneumatic with 2 lines according to ECE regulations with 2 channel EBS and RSS.
- Ø **Parking Brakes:** spring brakes with pneumatic controls.
- Ø **Suspensions:** pneumatic type with rising-lowering valve.
- Ø **Wheels:** disc 19.5 x 7.50 and M spigot.
- Ø **Tyres:** 265/70R19.5 143/141J twin.
- Ø **King Pin:** 2" demountable from below.
- Ø **Landing legs:** two speed with rocking feet.
- Ø **Body:** box unit for livestock 2+2, 2+3, 3+3, 3+4 or 4+4 loading decks with hydraulic controls, raising lowering roof on lower part and on goose neck, side doors and back doors, wide tool boxes under the body, internal and external working lights.
- Ø **Loading deck:** low loading capacity = 970 mm height, internal working height = 3200 mm.
- Ø **Electrohydraulic system:** completed with automatic safety device in accordance with Machines Directive and Work Safety Institute. (approval TUV n° 24 03 9761 002)
- Ø **Loading ramp:** hydraulically controlled, anti-slip, with incorporated side guards and working as barn doors if necessary
- Ø **Partition gates:** in aluminium or zinc coated steel with over-flap for larger animals.

OPTIONALS

- Ø Vents on sided to be closed with aluminium flaps (+300 Kg);
- Ø Automatic drinking system with water tank (+500 Kg);
- Ø Heating system for drinking system